


DIMENSION:(MM)

- T:0.5 ± 0.03
- L:20.7 ± 0.35
- E:13.0 ± 0.25
- D:1.2 ± 0.2
- W:2.8 ± 0.2
- IS:4.4 ± 0.3
- WS:3.4 ± 0.3
- H:4.1 ± 0.25
- H1:3.2 ± 0.25
- t:2.0 ± 0.25

MATERIAL:BRASS
 THICKNESS:0.5
 HARDNESS:H
 PLATING:TIN 40u" MIN
 WIRE RANGE:(AWG)16-20
 INSULATION O.D.:2.3 MAX.
 RATED VOLTAGE:AC,DC,250V
 CURRENT RATED:AC,DC,10A
 TEMPERATURE RANGE : -25°C TO +85°C

RoHS
Compliant

| REV. | REVISION RECORD | DATE | General Tolerance | |  |
|------|-----------------|-----------|-------------------|------------|---|
| A | Original | 02/11/22" | LINEAR | 0.0 ±0.35 | |
| | | | | 0.00 ±0.20 | |
| | | | UNIT:mm | | TITLE: Terminal Male Type 20.7L (Mate for HTM001-504) |
| | | | A4 | NAME | |
| | | | APPROVED | KELLY | |
| | | | DESIGNER | GRACE | |
| | | | DRAWN | JSMAY | DWG.NO: TRM001-504 |
| | | | | | SCALE 1 : 1 |
| | | | | | SHEET 1 OF 1 |
| | | | | | REV. A |